according to Regulation (EC) No. 1907/2006 - SE (Commission Regulation (EU) 2020/878)



**ISOFLEX TOPAS NB 152** 

Version Revision Date: Date of last issue: 2022-04-04 Print Date: 2023-

6.0 2023-07-27 Date of first issue: 2016-03-31 07-27

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : ISOFLEX TOPAS NB 152

Article-No. : 004145

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Grease

Substance/Mixture

Recommended restrictions

on use

Restricted to professional users.

1.3 Details of the supplier of the safety data sheet

Company : Klüber Lubrication München GmbH & Co. KG

Geisenhausenerstr. 7 81379 München Deutschland

Tel.: +49 (0) 89 7876 0 Fax: +49 (0) 89 7876 333

info@klueber.com

E-mail address of person : mcm@klueber.com

responsible for the SDS Material Compliance Management

National contact : Klüber Lubrication Nordic A/S

Vasagatan 36 111 20 Stockholm

Sweden

Tel: +46 8 59098600 Fax: +46 8 59098601 klueber.se@klueber.com

1.4 Emergency telephone number

Emergency telephone

number

112 - ask for poison information

+49 89 7876 700 (24 hrs)

according to Regulation (EC) No. 1907/2006 - SE (Commission Regulation (EU) 2020/878)



#### **ISOFLEX TOPAS NB 152**

Version Revision Date: Date of last issue: 2022-04-04 Print Date: 2023-

6.0 2023-07-27 Date of first issue: 2016-03-31 07-27

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

#### Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4 H302: Harmful if swallowed.

Acute toxicity, Category 4 H332: Harmful if inhaled.

#### 2.2 Label elements

### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :

Signal word : Warning

Hazard statements : H302 + H332 Harmful if swallowed or if inhaled.

Precautionary statements : Prevention:

P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this

product.

P271 Use only outdoors or in a well-ventilated

area.

Response:

P301 + P312 + P330 IF SWALLOWED: Call a POISON

CENTER/ doctor if you feel unwell. Rinse

mouth.

P304 + P340 + P312 IF INHALED: Remove person to fresh

air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel

unwell.

### Hazardous components which must be listed on the label:

Reaction mixture of hydrogenated tallow alkyl amines with sebacic acid and barium hydroxide

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.



according to Regulation (EC) No. 1907/2006 - SE (Commission Regulation (EU) 2020/878)



# **ISOFLEX TOPAS NB 152**

Version Revision Date: Date of last issue: 2022-04-04 Print Date: 2023-

6.0 2023-07-27 Date of first issue: 2016-03-31 07-27

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

Chemical nature : Synthetic hydrocarbon oil barium complex soap

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	specific concentration limit M-Factor Notes Acute toxicity estimate	Concentration (% w/w)
Reaction mixture of hydrogenated tallow alkyl amines with sebacic acid and barium hydroxide	1282612-27-4 433-080-4 056-002-00-7 01-0000017924-63- 0001	Acute Tox.4; H302 Acute Tox.4; H332	Note A, Note 1	>= 30 - < 50
Isotridecanol, ethoxylated	69011-36-5 500-241-6 01-2119976362-32- XXXX	Aquatic Acute1; H400 Aquatic Chronic3; H412	M-Factor: 1/	>= 0,1 - < 0,25

For explanation of abbreviations see section 16.

### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures



according to Regulation (EC) No. 1907/2006 - SE (Commission Regulation (EU) 2020/878)



**ISOFLEX TOPAS NB 152** 

Version Revision Date: Date of last issue: 2022-04-04 Print Date: 2023-

6.0 2023-07-27 Date of first issue: 2016-03-31 07-27

If inhaled : Remove person to fresh air. If signs/symptoms continue, get

medical attention.

Keep patient warm and at rest.

If unconscious, place in recovery position and seek medical

advice.

Keep respiratory tract clear.

If breathing is irregular or stopped, administer artificial

respiration.

In case of skin contact : Take off all contaminated clothing immediately.

Wash off immediately with soap and plenty of water. Get medical attention immediately if irritation develops and

persists.

Wash clothing before reuse.

Thoroughly clean shoes before reuse.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids,

for at least 10 minutes. Seek medical advice.

If swallowed : Move the victim to fresh air.

If unconscious, place in recovery position and seek medical

advice.

Keep respiratory tract clear.

Do not induce vomiting without medical advice.

Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Inhalation may provoke the following symptoms:

Headache Nausea

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

# **SECTION 5: Firefighting measures**

5.1 Extinguishing media

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or

carbon dioxide.

Unsuitable extinguishing

media

High volume water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion : Carbon oxides



according to Regulation (EC) No. 1907/2006 - SE (Commission Regulation (EU) 2020/878)



**ISOFLEX TOPAS NB 152** 

Version Revision Date: Date of last issue: 2022-04-04 Print Date: 2023-

6.0 2023-07-27 Date of first issue: 2016-03-31 07-27

products Nitrogen oxides (NOx)

Metal oxides

5.3 Advice for firefighters

Special protective equipment:

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment. Exposure to decomposition products may be a hazard to health.

Further information : Standard procedure for chemical fires.

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.

Use the indicated respiratory protection if the occupational exposure limit is exceeded and/or in case of product release

(dust).

Do not breathe vapours, aerosols.

Refer to protective measures listed in sections 7 and 8.

#### 6.2 Environmental precautions

Environmental precautions : Try to prevent the material from entering drains or water

courses.

Local authorities should be advised if significant spillages

cannot be contained.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Clean up promptly by sweeping or vacuum.

Keep in suitable, closed containers for disposal.

### 6.4 Reference to other sections

For personal protection see section 8.

# **SECTION 7: Handling and storage**

# 7.1 Precautions for safe handling

Advice on safe handling : Avoid contact with skin and eyes.

For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Wash hands and face before breaks and immediately after

handling the product.

Do not get in eyes or mouth or on skin.



according to Regulation (EC) No. 1907/2006 - SE (Commission Regulation (EU) 2020/878)



**ISOFLEX TOPAS NB 152** 

Version Revision Date: Date of last issue: 2022-04-04 Print Date: 2023-

6.0 2023-07-27 Date of first issue: 2016-03-31 07-27

Do not get on skin or clothing.

Do not ingest. Do not repack.

These safety instructions also apply to empty packaging which

may still contain product residues. Keep container closed when not in use.

Hygiene measures : Wash face, hands and any exposed skin thoroughly after

handling.

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Store in original container. Keep container closed when not in use. Keep in a dry, cool and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with the particular national regulations. Keep in properly labelled containers.

7.3 Specific end use(s)

Specific use(s) : Specific instructions for handling, not required.

# **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

Contains no substances with occupational exposure limit values.

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
bis(4-(1,1,3,3- tetramethylbutyl)phen yl)amine	Workers	Inhalation	Long-term systemic effects	49,3 mg/m3
	Workers	Dermal	Long-term systemic effects	14 mg/kg bw/day
Isotridecanol, ethoxylated	Workers	Inhalation	Long-term systemic effects	37 mg/m3
	Workers	Dermal	Long-term systemic effects	263 mg/kg bw/day

# Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Isotridecanol, ethoxylated	Fresh water	0,00436 mg/l
	Marine water	0,000436 mg/l
	Microbiological Activity in Sewage Treatment Systems	4,35 mg/l
	Fresh water sediment	0,119 mg/kg
	Marine sediment	0,012 mg/kg



according to Regulation (EC) No. 1907/2006 - SE (Commission Regulation (EU) 2020/878)



**ISOFLEX TOPAS NB 152** 

Version Revision Date: Date of last issue: 2022-04-04 Print Date: 2023-

6.0 2023-07-27 Date of first issue: 2016-03-31 07-27

Soil 0,021 mg/kg

#### 8.2 Exposure controls

### **Engineering measures**

Handle only in a place equipped with local exhaust (or other appropriate exhaust).

Personal protective equipment

Eye/face protection : Safety glasses with side-shields

Hand protection

Material : Nitrile rubber
Break through time : > 10 min
Protective index : Class 1

Remarks : For prolonged or repeated contact use protective gloves. The

break through time depends amongst other things on the material, the thickness and the type of glove and therefore

has to be measured for each case.

The selected protective gloves have to satisfy the

specifications of Regulation (EU) 2016/425 and the standard

EN 374 derived from it.

Skin and body protection : Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to

the specific work-place.

Respiratory protection : Not required; except in case of aerosol formation.

Filter type : Filter type P

Protective measures : The type of protective equipment must be selected according

to the concentration and amount of the dangerous substance

at the specific workplace.

# **SECTION 9: Physical and chemical properties**

### 9.1 Information on basic physical and chemical properties

Physical state : paste

Colour : beige

Odour : characteristic

Odour Threshold : No data available

according to Regulation (EC) No. 1907/2006 - SE (Commission Regulation (EU) 2020/878)



**ISOFLEX TOPAS NB 152** 

Version Revision Date: Date of last issue: 2022-04-04 Print Date: 2023-

6.0 2023-07-27 Date of first issue: 2016-03-31 07-27

Melting point/range : No data available

Boiling point/boiling range : No data available

Flammability (solid, gas) : Combustible Solids

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Flash point : Not applicable

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : Not applicable

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : Not applicable

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Vapour pressure : < 0,001 hPa (20 °C)

Relative density : 0,96 (20 °C)

Reference substance: Water The value is calculated

Density : 0,96 g/cm3

(20 °C)

Bulk density : No data available

Relative vapour density : No data available

9.2 Other information

Explosives : Not explosive

according to Regulation (EC) No. 1907/2006 - SE (Commission Regulation (EU) 2020/878)



**ISOFLEX TOPAS NB 152** 

Version Revision Date: Date of last issue: 2022-04-04 Print Date: 2023-

6.0 2023-07-27 Date of first issue: 2016-03-31 07-27

Oxidizing properties : No data available

Self-ignition : No data available

Evaporation rate : No data available

Sublimation point : No data available

# **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No hazards to be specially mentioned.

### 10.2 Chemical stability

Stable under normal conditions.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid : No conditions to be specially mentioned.

10.5 Incompatible materials

Materials to avoid : No materials to be especially mentioned.

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

# **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

### **Acute toxicity**

**Product:** 

Acute oral toxicity : Remarks: Harmful if swallowed.

Acute toxicity estimate: 1.466 mg/kg

Method: Calculation method

Acute inhalation toxicity : Remarks: Harmful by inhalation.

Acute toxicity estimate: 4,4 mg/l



according to Regulation (EC) No. 1907/2006 - SE (Commission Regulation (EU) 2020/878)



**ISOFLEX TOPAS NB 152** 

Version Revision Date: Date of last issue: 2022-04-04 Print Date: 2023-

6.0 2023-07-27 Date of first issue: 2016-03-31 07-27

Exposure time: 4 h

Test atmosphere: dust/mist Method: Calculation method

Acute dermal toxicity : Remarks: This information is not available.

**Components:** 

Reaction mixture of hydrogenated tallow alkyl amines with sebacic acid and barium hydroxide:

Acute oral toxicity : LD50 (Rat): Assessment: The component/mixture is

moderately toxic after single ingestion.

Acute inhalation toxicity : Assessment: The component/mixture is moderately toxic after

short term inhalation.

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg

Method: OECD Test Guideline 402

GLP: yes

Assessment: The substance or mixture has no acute dermal

toxicity

Isotridecanol, ethoxylated:

Acute oral toxicity : LD50 (Rat): > 10.000 mg/kg

Method: OECD Test Guideline 401

Assessment: The substance or mixture has no acute oral

toxicity

Acute dermal toxicity : LD50 (Rat): > 5.960 mg/kg

Method: OECD Test Guideline 402

Skin corrosion/irritation

**Product:** 

Remarks : This information is not available.

**Components:** 

Reaction mixture of hydrogenated tallow alkyl amines with sebacic acid and barium hydroxide:

Species : Rabbit

Assessment : No skin irritation

Method : OECD Test Guideline 404

Result : No skin irritation

GLP : yes



according to Regulation (EC) No. 1907/2006 - SE (Commission Regulation (EU) 2020/878)



### **ISOFLEX TOPAS NB 152**

Version Revision Date: Date of last issue: 2022-04-04 Print Date: 2023-

6.0 2023-07-27 Date of first issue: 2016-03-31 07-27

### Serious eye damage/eye irritation

**Product:** 

Remarks : This information is not available.

### **Components:**

Reaction mixture of hydrogenated tallow alkyl amines with sebacic acid and barium hydroxide:

Species : Rabbit

Assessment : No eye irritation

Method : OECD Test Guideline 405

Result : No eye irritation

GLP : yes

### Respiratory or skin sensitisation

**Product:** 

Remarks : This information is not available.

### **Components:**

Reaction mixture of hydrogenated tallow alkyl amines with sebacic acid and barium hydroxide:

Test Type : Maximisation Test

Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

Result : Does not cause skin sensitisation.

GLP : yes

#### Isotridecanol, ethoxylated:

Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

Result : Does not cause skin sensitisation.

### Germ cell mutagenicity

**Product:** 

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

according to Regulation (EC) No. 1907/2006 - SE (Commission Regulation (EU) 2020/878)



**ISOFLEX TOPAS NB 152** 

Version Revision Date: Date of last issue: 2022-04-04 Print Date: 2023-

6.0 2023-07-27 Date of first issue: 2016-03-31 07-27

**Components:** 

Reaction mixture of hydrogenated tallow alkyl amines with sebacic acid and barium

hydroxide:

Genotoxicity in vitro : Test Type: Ames test

Method: OECD Test Guideline 471

Result: negative GLP: yes

**Product:** 

Carcinogenicity

Remarks : No data available

Reproductive toxicity

**Product:** 

Effects on fertility : Remarks: No data available

Effects on foetal

development

: Remarks: No data available

**Components:** 

Isotridecanol, ethoxylated:

Effects on foetal : Species: Rat

development General Toxicity Maternal: NOAEL: > 250 mg/kg body weight

Developmental Toxicity: NOAEL: > 250 mg/kg body weight

Method: OECD Test Guideline 416

Result: No effects on fertility and early embryonic

development were detected.

STOT - single exposure

**Product:** 

Remarks : No data available

STOT - repeated exposure

**Product:** 

Remarks : No data available

Repeated dose toxicity

Product:

Remarks : This information is not available.



according to Regulation (EC) No. 1907/2006 - SE (Commission Regulation (EU) 2020/878)



### **ISOFLEX TOPAS NB 152**

Version Revision Date: Date of last issue: 2022-04-04 Print Date: 2023-

6.0 2023-07-27 Date of first issue: 2016-03-31 07-27

### **Components:**

Reaction mixture of hydrogenated tallow alkyl amines with sebacic acid and barium hydroxide:

NOAEL : 150 mg/kg

### **Aspiration toxicity**

#### **Product:**

This information is not available.

#### 11.2 Information on other hazards

# **Endocrine disrupting properties**

**Product:** 

Assessment : The substance/mixture does not contain components

considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

#### **Further information**

**Product:** 

Remarks : Information given is based on data on the components and

the toxicology of similar products.

# **SECTION 12: Ecological information**

#### 12.1 Toxicity

**Product:** 

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other :

aquatic invertebrates

Remarks: No data available

Toxicity to algae/aquatic

plants

Remarks: No data available

Toxicity to microorganisms

Remarks: No data available

according to Regulation (EC) No. 1907/2006 - SE (Commission Regulation (EU) 2020/878)



**ISOFLEX TOPAS NB 152** 

Version Revision Date: Date of last issue: 2022-04-04 Print Date: 2023-

6.0 2023-07-27 Date of first issue: 2016-03-31 07-27

### **Components:**

Reaction mixture of hydrogenated tallow alkyl amines with sebacic acid and barium hydroxide:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 100 mg/l

Exposure time: 96 h Test Type: static test

Method: OECD Test Guideline 203

GLP: yes

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h
Test Type: Immobilization

Method: OECD Test Guideline 202

GLP: yes

Toxicity to algae/aquatic

plants

ErC50 (Desmodesmus subspicatus (green algae)): > 100 mg/l

Exposure time: 72 h

Test Type: Growth inhibition Method: OECD Test Guideline 201

GLP: yes

Toxicity to microorganisms : EC50 (Bacteria): > 1.000 mg/l

Exposure time: 3 h

Test Type: Respiration inhibition Method: OECD Test Guideline 209

GLP: yes

Isotridecanol, ethoxylated:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 1,1 mg/l

Exposure time: 96 h
Test Type: semi-static test

Method: OECD Test Guideline 203

GLP: yes

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 0,544 mg/l

Exposure time: 48 h Test Type: semi-static test

Method: OECD Test Guideline 202

GLP: yes

Toxicity to algae/aquatic

plants

EL50 (Desmodesmus subspicatus (green algae)): 3,4 mg/l

Exposure time: 72 h Test Type: static test

Method: Regulation (EC) No. 440/2008, Annex, C.3

M-Factor (Acute aquatic

toxicity)

: 1



according to Regulation (EC) No. 1907/2006 - SE (Commission Regulation (EU) 2020/878)



**ISOFLEX TOPAS NB 152** 

Version Date of last issue: 2022-04-04 Print Date: 2023-Revision Date:

2023-07-27 Date of first issue: 2016-03-31 6.0 07-27

**Ecotoxicology Assessment** 

Chronic aquatic toxicity Harmful to aquatic life with long lasting effects.

12.2 Persistence and degradability

**Product:** 

Biodegradability Remarks: No data available

Physico-chemical

removability

Remarks: No data available

**Components:** 

Reaction mixture of hydrogenated tallow alkyl amines with sebacic acid and barium

hydroxide:

Biodegradability Test Type: Primary biodegradation

> Inoculum: activated sludge Result: Not rapidly biodegradable

Biodegradation: 16,8 % Exposure time: 28 d

Method: OECD Test Guideline 301F

GLP: yes

Isotridecanol, ethoxylated:

Biodegradability Test Type: Primary biodegradation

> Inoculum: activated sludge Result: rapidly biodegradable Biodegradation: > 60 %

Exposure time: 28 d

Method: OECD Test Guideline 301B

12.3 Bioaccumulative potential

**Product:** 

Bioaccumulation Remarks: This mixture contains no substance considered to

be persistent, bioaccumulating and toxic (PBT).

This mixture contains no substance considered to be very

persistent and very bioaccumulating (vPvB).

**Components:** 

Reaction mixture of hydrogenated tallow alkyl amines with sebacic acid and barium

hydroxide:

Partition coefficient: n-

octanol/water

: log Pow: 0,9 - 18

Isotridecanol, ethoxylated:



according to Regulation (EC) No. 1907/2006 - SE (Commission Regulation (EU) 2020/878)



**ISOFLEX TOPAS NB 152** 

Version Revision Date: Date of last issue: 2022-04-04 Print Date: 2023-

6.0 2023-07-27 Date of first issue: 2016-03-31 07-27

Partition coefficient: n-

octanol/water

: log Pow: 4,73

#### 12.4 Mobility in soil

**Product:** 

Mobility : Remarks: No data available

Distribution among

environmental compartments

Remarks: No data available

#### 12.5 Results of PBT and vPvB assessment

**Product:** 

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

#### 12.6 Endocrine disrupting properties

**Product:** 

Assessment : The substance/mixture does not contain components

considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

# 12.7 Other adverse effects

**Product:** 

Additional ecological

information

: No information on ecology is available.

# **SECTION 13: Disposal considerations**

# 13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water

courses or the soil.

Do not dispose of with domestic refuse.

Dispose of as hazardous waste in compliance with local and

national regulations.

Waste codes should be assigned by the user based on the

application for which the product was used.



according to Regulation (EC) No. 1907/2006 - SE (Commission Regulation (EU) 2020/878)



**ISOFLEX TOPAS NB 152** 

Version Revision Date: Date of last issue: 2022-04-04 Print Date: 2023-

6.0 2023-07-27 Date of first issue: 2016-03-31 07-27

Contaminated packaging : Packaging that is not properly emptied must be disposed of as

the unused product.

Dispose of waste product or used containers according to

local regulations.

The following Waste Codes are only suggestions:

Waste Code : used product, unused product

12 01 12\*, spent waxes and fats

uncleaned packagings

15 01 10\*, packaging containing residues of or contaminated

by hazardous substances

# **SECTION 14: Transport information**

### 14.1 UN number or ID number

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

### 14.2 UN proper shipping name

ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

### 14.3 Transport hazard class(es)

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

### 14.4 Packing group

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA (Cargo) : Not regulated as a dangerous good

IATA (Passenger) : Not regulated as a dangerous good



according to Regulation (EC) No. 1907/2006 - SE (Commission Regulation (EU) 2020/878)



**ISOFLEX TOPAS NB 152** 

Date of last issue: 2022-04-04 Print Date: 2023-Version Revision Date:

2023-07-27 Date of first issue: 2016-03-31 6.0 07-27

14.5 Environmental hazards

**ADR** Not regulated as a dangerous good **RID** Not regulated as a dangerous good **IMDG** Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

**SECTION 15: Regulatory information** 

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

mixtures and articles (Annex XVII)

Not applicable

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

(EU SVHC)

This product does not contain substances of very high concern

(Regulation (EC) No

1907/2006 (REACH), Article 57).

Regulation (EC) No 1005/2009 on substances that

deplete the ozone layer

(EC 1005/2009)

: Not applicable

Regulation (EU) 2019/1021 on persistent organic

pollutants (recast)

(EU POP)

: Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and

import of dangerous chemicals

(EU PIC)

Not applicable

Regulation (EU) 2019/1148 on the marketing and use of : Not applicable

explosives precursors

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous

Not applicable



according to Regulation (EC) No. 1907/2006 - SE (Commission Regulation (EU) 2020/878)



#### **ISOFLEX TOPAS NB 152**

Version Revision Date: Date of last issue: 2022-04-04 Print Date: 2023-

6.0 2023-07-27 Date of first issue: 2016-03-31 07-27

substances.

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial

emissions (integrated pollution prevention and control)

Not applicable

### Other regulations:

Hygiene limits (AFS 2018:1), provisions - Occupational Safety and Health Administration's provisions on hygiene limits and general advice on the application of the provisions.

Take note of the Swedish Work Environment Authority regulations on Chemical Hazards in the Working Environment (AFS 2011:19)

#### 15.2 Chemical safety assessment

This information is not available.

#### **SECTION 16: Other information**

#### **Full text of H-Statements**

H302 : Harmful if swallowed. H332 : Harmful if inhaled. H400 : Very toxic to aquatic life.

H412 : Harmful to aquatic life with long lasting effects.

### Full text of other abbreviations

Note 1 : The concentration stated or, in the absence of such

concentrations, the generic concentrations set out in this Regulation are the percentages by weight of the metallic element calculated with reference to the total weight of the

mixture.

Note A : Without prejudice to Article 17(2), the name of the substance

must appear on the label in the form of one of the designations given in Part 3. In Part 3, use is sometimes made of a general description such as "... compounds" or "... salts". In this case, the supplier is required to state on the label the correct name, due account being taken of section

1.1.1.4.

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada);



according to Regulation (EC) No. 1907/2006 - SE (Commission Regulation (EU) 2020/878)



### **ISOFLEX TOPAS NB 152**

Version Revision Date: Date of last issue: 2022-04-04 Print Date: 2023-

6.0 2023-07-27 Date of first issue: 2016-03-31 07-27

ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID -Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### **Further information**

#### Classification of the mixture:

### Classification procedure:

Acute Tox. 4	H302	Calculation method
Acute Tox. 4	H332	Calculation method

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.



according to Regulation (EC) No. 1907/2006 - SE (Commission Regulation (EU) 2020/878)



**ISOFLEX TOPAS NB 152** 

Version Revision Date: Date of last issue: 2022-04-04 Print Date: 2023-6.0

Date of first issue: 2016-03-31 2023-07-27 07-27