

TECHNICAL DATA

Precision Silicone Spray (Formerly SL SPRAY)

Silicone Lubricant Spray

Description

ROCOL Precision Silicone Spray is a carefully blended mix of silicone fluids designed to give light lubrication in the food, chemical and other clean industries or wherever a clear film is preferred. It is also suitable for use as a release agent.

ROCOL Precision Silicone Spray is manufactured from F.D.A. listed ingredients and is U.S.D.A. H1 authorised.

Outstanding Features

- ? **Clean, non-toxic lubricating film**
- ? **Light film - does not easily transfer**
- ? **Resists oxidation and corrosion**
- ? **F.D.A. listed ingredients - U.S.D.A. H1 authorised**

Directions for use

Shake well, hold upright and spray onto surfaces to be lubricated from a distance of about 15-30 cm (6-12 inches). Ensure adequate ventilation. Do not spray on a naked flame or any incandescent material.

Technical Data (typical values)

<i>Propellant</i>	: Hydrocarbon
<i>Solvent</i>	: Isoparaffinic hydrocarbon
<i>Base lubricant</i>	: Blend of silicone oils
<i>Temperature range</i>	: -50°C to 200°C
<i>Storage</i>	: Storage temperature should be kept below 50°C. Storage area should be out of direct sunlight.

Further Technical Data and Health and Safety information (MSDS) is available from:

