



SAFETY DATA SHEET ABSODAN Plus

According to the REACH etc. (Amendment etc.) (EU Exit) Regulations 2020 No. 1577, as amended.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

| | |
|------------------------------------|---|
| Product name | ABSODAN Plus |
| Substance Name | Diatomaceous earth (calcined) |
| Synonyms; trade names | Diatomaceous earth (moler) granulated, calcined |
| EU REACH registration notes | Exempted in accordance with REACH Annex V.7 |
| CAS number | 91053-39-3 |
| EC number | 293-303-4 |

1.2. Relevant identified uses of the substance or mixture and uses advised against

| | |
|------------------------|------------|
| Identified uses | Absorbents |
|------------------------|------------|

1.3. Details of the supplier of the safety data sheet

| | |
|-----------------------|--|
| Supplier | Imerys Minerals Ltd Imerys Technology Centre UK Par Moor Road Par, Cornwall England PL24 2SQ Tel. +44(0)1726 818000 Fax. +44(0)1726 811200 SDS.expert@imerys.com |
| Contact person | Please approach your usual Imerys contact in the first instance. |
| Manufacturer | Imerys Industrial Minerals Denmark A/S Kønsborgvej 9 DK-7884 Fur +45 97593222 (during office hours) Tel. +45 97593222 (during office hours) SDS.expert@imerys.com |

1.4. Emergency telephone number

| | |
|----------------------------|---------------------------|
| Emergency telephone | CHEMTREC + 1 703 527 3887 |
|----------------------------|---------------------------|

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (SI 2019 No. 720)

| | |
|------------------------------|----------------|
| Physical hazards | Not Classified |
| Health hazards | Not Classified |
| Environmental hazards | Not Classified |

ABSODAN Plus

Human health This product does not meet the criteria for classification as hazardous as defined in the Regulation EC 1272/2008. Depending on the type of handling and use (e.g. grinding, drying), airborne respirable crystalline silica may be generated. Prolonged and/or massive inhalation of respirable crystalline silica dust may cause lung fibrosis, commonly referred to as silicosis. Principal symptoms of silicosis are cough and breathlessness. Occupational exposure to respirable crystalline silica dust should be monitored and controlled.

Environmental The product is not expected to be hazardous to the environment.

Physicochemical This product is an inorganic substance and does not meet the criteria for PBT or vPvB in accordance with Annex XIII of REACH. This product should be handled with care to avoid dust generation.

2.2. Label elements

EC number 293-303-4

Hazard statements NC Not Classified

2.3. Other hazards

This substance is not classified as PBT or vPvB according to current UK criteria.

Endocrine disrupting properties Available data for the substance have been considered against the criteria laid down in Regulations ((EC) No 1907/2006, (EU) 2017/2100, (EU) 2018/605) and found not to apply.

SECTION 3: Composition/information on ingredients

3.1. Substances

| | |
|-------------------------------------|----------------------|
| Diatomaceous Earth, Calcined | 100% |
| CAS number: 91053-39-3 | EC number: 293-303-4 |
| Classification | |
| Not Classified | |

The full text for all hazard statements is displayed in Section 16.

Product name ABSODAN Plus

EU REACH registration notes Exempted in accordance with REACH Annex V.7

CAS number 91053-39-3

EC number 293-303-4

Ingredient notes This is a UVCB substance. This product does not contain any SVHC substances at levels greater than 0.1 % by weight.

Composition comments This product contains less than 1% crystalline silica (fine fraction) consisting of cristobalite (fine fraction) and quartz (fine fraction). Cristobalite: CAS-No.: 14464-46-1 EC No.: 238-455-4. Quartz: CAS-No.: 14808-60-7 EC No.: 238-878-4.
The classification of the product is shown in section 2 of this safety data sheet.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information No acute and delayed symptoms and effects are observed.

Inhalation Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.

Ingestion Rinse mouth thoroughly with water. Get medical attention if any discomfort continues.

ABSODAN Plus

| | |
|-----------------------------------|---|
| Skin contact | Wash skin thoroughly with soap and water. Use suitable lotion to moisturise skin. |
| Eye contact | Do not rub eye. Rinse with copious quantities of water and seek medical attention if irritation persists. |
| Protection of first aiders | For personal protection, see Section 8. |

4.2. Most important symptoms and effects, both acute and delayed

| | |
|----------------------------|---|
| General information | The severity of the symptoms described will vary dependent on the concentration and the length of exposure. |
|----------------------------|---|

4.3. Indication of any immediate medical attention and special treatment needed

| | |
|-----------------------------|------------------------------|
| Notes for the doctor | No specific recommendations. |
|-----------------------------|------------------------------|

SECTION 5: Firefighting measures

5.1. Extinguishing media

| | |
|---------------------------------------|---|
| Suitable extinguishing media | This product is non-combustible. No specific extinguishing media is needed. Use fire-extinguishing media suitable for the surrounding fire. |
| Unsuitable extinguishing media | No restriction on the extinguishing media to be used. |

5.2. Special hazards arising from the substance or mixture

| | |
|-------------------------|--|
| Specific hazards | Non combustible. No hazardous thermal decomposition. |
|-------------------------|--|

5.3. Advice for firefighters

| | |
|---|---|
| Protective actions during firefighting | No specific fire-fighting protection is required. Use an extinguishing agent suitable for the surrounding fire. Product on floor when wetted will become slippery and may present a hazard; wear anti-slip boots. |
|---|---|

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

| | |
|-----------------------------|---|
| Personal precautions | Avoid airborne dust generation, wear personal protective equipment in compliance with national legislation. Product on floor when wetted will become slippery and may present a hazard; wear anti-slip boots. |
|-----------------------------|---|

6.2. Environmental precautions

| | |
|----------------------------------|--|
| Environmental precautions | Do not discharge into drains or watercourses or onto the ground. |
|----------------------------------|--|

6.3. Methods and material for containment and cleaning up

| | |
|--------------------------------|---|
| Methods for cleaning up | Avoid dry sweeping and use water spraying or vacuum cleaning systems to prevent airborne dust generation. Wear personal protective equipment in compliance with national legislation. Product on floor when wetted will become slippery and may present a hazard; wear anti-slip boots. |
|--------------------------------|---|

6.4. Reference to other sections

| | |
|------------------------------------|---|
| Reference to other sections | For personal protection, see Section 8. For waste disposal, see Section 13. |
|------------------------------------|---|

SECTION 7: Handling and storage

7.1. Precautions for safe handling

ABSODAN Plus

| | |
|---|---|
| Usage precautions | Avoid airborne dust generation. Provide appropriate exhaust ventilation at places where airborne dust is generated. In case of insufficient ventilation, wear suitable respiratory protective equipment. Handle packaged products carefully to prevent accidental bursting. If you require advice on safe handling techniques, please contact your supplier. Do not eat, drink and smoke in work areas; wash hands after use; remove contaminated clothing and protective equipment before entering eating areas. Product on floor when wetted will become slippery and may present a hazard; wear anti-slip boots. For personal protection, see Section 8. |
| Advice on general occupational hygiene | Keep dust levels to a minimum. Minimize dust generation. General occupational hygiene measures are required. These include good personal and housekeeping practices (i.e. regular cleaning with suitable cleaning devices). Shower and change clothes at end of work shift. Change work clothing daily before leaving workplace. |

7.2. Conditions for safe storage, including any incompatibilities

| | |
|----------------------------|--|
| Storage precautions | Store in a dry covered area. Minimise airborne dust generation and prevent wind dispersal during loading and unloading. Keep containers closed and store packaged products so as to prevent accidental bursting. Avoid contact with the following materials: Hydrofluoric acid |
|----------------------------|--|

7.3. Specific end use(s)

| | |
|--------------------------|---|
| Usage description | If you require advice on specific uses, please contact your supplier. |
|--------------------------|---|

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

A European Binding OEL (Occupational Exposure Limit) for respirable crystalline silica dust is set at 0.1 mg/m³ in the Directive (EU) 2017/2398, measured as an 8-hour TWA (Time Weighted Average).

Inorganic dust

Long-term exposure limit (8-hour TWA): WEL 4 mg/m³ respirable dust

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ inhalable dust

Quartz

Long-term exposure limit (8-hour TWA): WEL 0,1 mg/m³ respirable dust

Cristobalite

Long-term exposure limit (8-hour TWA): WEL 0,1 mg/m³ respirable dust

WEL = Workplace Exposure Limit.

| | |
|----------------------------|--|
| Ingredient comments | Maintain personal exposure below occupational exposure limits for dust (inhalable and respirable) as dictated in the national legislation. |
|----------------------------|--|

8.2. Exposure controls

Appropriate engineering controls

Minimise airborne dust generation. Use process enclosures, local exhaust ventilation or other engineering controls to keep airborne levels below specified exposure limits. If user operations generate dust, fumes or mist, use ventilation to keep exposure to airborne particles below the exposure limit. Apply organisational measures, e.g. by isolating personnel from dusty areas. Remove and wash soiled clothing. Observe any occupational exposure limits for the product or ingredients. .

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles or face shield. Contact lenses should not be worn when working with this product.

ABSODAN Plus

| | |
|--|---|
| Hand protection | Appropriate protection (e.g. gloves, barrier cream) is recommended for workers who suffer from dermatitis or sensitive skin. Wash hands at the end of each work session. It is recommended that gloves are made of the following material: Polyvinyl chloride (PVC). Neoprene. Rubber (natural, latex). |
| Other skin and body protection | For skin, normal work clothes are appropriate. |
| Hygiene measures | When using do not eat, drink or smoke. Wash at the end of each work shift and before eating, smoking and using the toilet. Use appropriate skin cream to prevent drying of skin. |
| Respiratory protection | Local ventilation to control airborne dust levels below occupational exposure limits is recommended. In case of exposure, where engineering controls are insufficient, the use of Respiratory Protective Equipment (RPE) is recommended. A risk assessment process must be followed to ensure adequate protection from the airborne dust. The type of RPE must suit the work situation and the specific requirements of the wearer. Other environmental conditions should also be considered. The minimum "Assigned Protection Factor" (APF) required will depend on the measured or predicted occupational exposure levels divided by the OEL detailed in section 8.1. Filters specified as FFP2 and P2 have an APF of 10. Correctly fitted, these would reduce the exposure to the wearer down to one tenth of the working atmosphere. Depending on the assessment of the exposure, a lesser or higher efficiency of filter may be required. The manufacturer's instructions and regulatory guidance regarding duration of use and correct fitting should be followed. The wearer of the selected RPE should receive training before use. |
| Environmental exposure controls | All ventilation systems should be filtered before discharge to atmosphere. Avoid releasing into the environment. Contain the spillage. |

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|---|---|
| Appearance | Granules. |
| Odour | Odourless. |
| Odour threshold | Not applicable. |
| pH | 5.5 @ 10 % Slurry. |
| Melting point | > 450°C EU Method A1 Read-across data: Kaolin |
| Initial boiling point and range | not applicable (Solid with a melting point > 450°C) |
| Flash point | not applicable (Solid with a melting point > 450°C) |
| Evaporation rate | not applicable (Solid with a melting point > 450°C) |
| Flammability (solid, gas) | Non flammable EU method A10 Read-across data: Kaolin |
| Upper/lower flammability or explosive limits | Non explosive (void of any chemical structures commonly associated with explosive properties) |
| Vapour pressure | not applicable (Solid with a melting point > 450°C) |
| Vapour density | not applicable (Solid with a melting point > 450°C) |
| Relative density | 2.3 |
| Solubility(ies) | Insoluble in water. |
| Partition coefficient | Not applicable (inorganic substance) |
| Auto-ignition temperature | Not auto flammable |

ABSODAN Plus

| | |
|----------------------------------|--|
| Decomposition Temperature | Not applicable (Solid with a melting point > 450°C) |
| Viscosity | Not applicable (Solid with a melting point > 450°C) |
| Explosive properties | There are no chemical groups present in the product that are associated with explosive properties. |
| Oxidising properties | There are no chemical groups present in the product that are associated with oxidising properties. |

9.2. Other information

| | |
|--------------------------|--------------------------|
| Other information | No information required. |
|--------------------------|--------------------------|

SECTION 10: Stability and reactivity

10.1. Reactivity

| | |
|-------------------|---|
| Reactivity | The following materials may react with the product: Hydrofluoric acid |
|-------------------|---|

10.2. Chemical stability

| | |
|------------------|---|
| Stability | Stable at normal ambient temperatures and when used as recommended. |
|------------------|---|

10.3. Possibility of hazardous reactions

| | |
|---|--|
| Possibility of hazardous reactions | Silicon tetrafluoride (SiF ₄) will form upon contact with hydrofluoric acid. |
|---|--|

10.4. Conditions to avoid

| | |
|----------------------------|---|
| Conditions to avoid | Avoid contact with the following materials: Hydrofluoric acid |
|----------------------------|---|

10.5. Incompatible materials

| | |
|---------------------------|-------------------|
| Materials to avoid | Hydrofluoric acid |
|---------------------------|-------------------|

10.6. Hazardous decomposition products

| | |
|---|--|
| Hazardous decomposition products | Silicon tetrafluoride (SiF ₄) will form upon contact with hydrofluoric acid. |
|---|--|

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

| | |
|-------------------------------------|--------------------|
| Notes (oral LD₅₀) | No data available. |
|-------------------------------------|--------------------|

Acute toxicity - dermal

| | |
|---------------------------------------|--------------------|
| Notes (dermal LD₅₀) | No data available. |
|---------------------------------------|--------------------|

Skin corrosion/irritation

| | |
|----------------------------------|--------------------|
| Skin corrosion/irritation | No data available. |
|----------------------------------|--------------------|

Serious eye damage/irritation

| | |
|--------------------------------------|--------------------|
| Serious eye damage/irritation | No data available. |
|--------------------------------------|--------------------|

Respiratory sensitisation

| | |
|----------------------------------|--------------------|
| Respiratory sensitisation | No data available. |
|----------------------------------|--------------------|

Skin sensitisation

| | |
|---------------------------|--------------------|
| Skin sensitisation | No data available. |
|---------------------------|--------------------|

Germ cell mutagenicity

| | |
|----------------|--------------------|
| Summary | No data available. |
|----------------|--------------------|

ABSODAN Plus

Carcinogenicity

Carcinogenicity This product does not meet the criteria for classification as hazardous as defined in the Regulation EC 1272/2008.

Reproductive toxicity

Summary No data available.

Specific target organ toxicity - single exposure

Summary No data available.

Specific target organ toxicity - repeated exposure

Summary No data available.

Aspiration hazard

Summary No data available.

Inhalation Dust in high concentrations may irritate the respiratory system.

Ingestion No harmful effects expected from quantities likely to be ingested by accident.

Skin contact Prolonged contact may cause dryness of the skin.

Eye contact Particles in the eyes may cause irritation and smarting.

Endocrine disrupting properties Available data for the substance have been considered against the criteria laid down in Regulations ((EC) No 1907/2006, (EU) 2017/2100, (EU) 2018/605) and found not to apply

Other information None

Toxicological information on ingredients.

Diatomaceous Earth, Calcined

Acute toxicity - oral

Notes (oral LD₅₀) No data available.

Acute toxicity - dermal

Notes (dermal LD₅₀) No data available.

Serious eye damage/irritation

Summary No data available.

Respiratory sensitisation

Summary No data available.

Skin sensitisation

Summary No data available.

Germ cell mutagenicity

Summary No data available.

Carcinogenicity

Summary This product does not meet the criteria for classification as hazardous as defined in the Regulation EC 1272/2008.

Reproductive toxicity

Summary No data available.

Specific target organ toxicity - single exposure

ABSODAN Plus

Summary No data available.

Specific target organ toxicity - repeated exposure

Summary No data available.

Aspiration hazard

Summary No data available.

SECTION 12: Ecological information

Ecotoxicity The product components are not classified as environmentally hazardous. However, large or frequent spills may have hazardous effects on the environment.

12.1. Toxicity

Acute aquatic toxicity

Acute toxicity - fish Not known.

Acute toxicity - aquatic invertebrates Not known.

Acute toxicity - aquatic plants Not known.

Ecological information on ingredients.

Diatomaceous Earth, Calcined

Acute aquatic toxicity

Acute toxicity - fish Not known.

Acute toxicity - aquatic invertebrates Not known.

Acute toxicity - aquatic plants Not known.

12.2. Persistence and degradability

Persistence and degradability The product is not biodegradable.

Ecological information on ingredients.

Diatomaceous Earth, Calcined

Persistence and degradability The product is not biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential The product does not contain any substances expected to be bioaccumulating.

Partition coefficient Not applicable (inorganic substance)

Ecological information on ingredients.

Diatomaceous Earth, Calcined

Bioaccumulative potential The product does not contain any substances expected to be bioaccumulating.

Partition coefficient Not applicable (inorganic substance)

12.4. Mobility in soil

Mobility The product is insoluble in water.

ABSODAN Plus

14.6. Special precautions for user

Not applicable. Avoid any release of dust during transportation, by using air-tight tanks for powders and covered trucks for other dry forms.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code No information required.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations EH40/2005 Workplace exposure limits.
Health and Safety at Work etc. Act 1974 (as amended).
The Control of Substances Hazardous to Health Regulations 2002 (SI 2002 No. 2677) (as amended).

EU legislation Exempted in accordance with REACH Annex V.7

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
CAS: Chemical Abstracts Service.
EC: European Commission
EC₅₀: 50% of maximal Effective Concentration.
FFP: Filtering Face Piece
IMDG: International Maritime Dangerous Goods.
IATA: International Air Transport Association.
LC50: Lethal Concentration to 50 % of a test population.
OECD: Organisation for Economic Co-operation and Development
OEL: Occupational Exposure Limit
PBT: Persistent, Bioaccumulative and Toxic substance.
vPvB: Very Persistent and Very Bioaccumulative.
REACH: The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020 No. 1577.
RID: European Agreement concerning the International Carriage of Dangerous Goods by Rail.
SDS: Safety Data Sheet
TWA: Time Weighted Average
UVCB - Unknown or variable composition, complex reaction products or Biological materials.

ABSODAN Plus

General information

Workers must be informed of the presence of crystalline silica and trained in the proper use and handling of this product as required under applicable regulations. A multi-sectoral social dialogue agreement on Workers Health Protection through the Good Handling and Use of Crystalline Silica and Products Containing it was signed on 25 April 2006. This autonomous agreement, which receives the European Commission's financial support, is based on a Good Practices Guide. The requirements of the Agreement came into force on 25 October 2006. The Agreement was published in the Official Journal of the European Union (2006/C 279/02). The text of the Agreement and its annexes, including the Good Practices Guide, are available from <http://www.nepsi.eu> and provide useful information and guidance for the handling of products containing crystalline silica (fine fraction). Literature references are available on request from EUROSIL, the European Association of Industrial Silica Producers. Prolonged and/or massive exposure to respirable crystalline silica-containing dust may cause silicosis, a nodular pulmonary fibrosis caused by deposition in the lungs of fine respirable particles of crystalline silica. In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However it pointed out that not all industrial circumstances, nor all crystalline silica types, were to be incriminated. (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In 2009, in the Monographs 100 series, IARC confirmed its classification of Silica Dust, Crystalline, in the form of Quartz and Cristobalite (IARC Monographs, Volume 100C, 2012). In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003). So there is a body of evidence supporting the fact that increased cancer risk would be limited to people already suffering from silicosis. Worker protection against silicosis should be assured by respecting the existing regulatory occupational exposure limits and implementing additional risk management measures where required. Health & Safety Executive: Detailed reviews of the scientific evidence on the health effects of crystalline silica have been published by HSE (Health and Safety Executive, UK) in the Hazard Assessment Documents EH75/4 (2002) and EH75/5 (2003). The HSE points out on its website that "Workers exposed to fine dust containing quartz are at risk of developing a chronic and possibly severely disabling lung disease known as "silicosis"." In addition to silicosis, there is now evidence that heavy and prolonged workplace exposure to dust containing crystalline silica can lead to an increased risk of lung cancer. The evidence suggests that an increased risk of lung cancer is likely to occur only in those workers who have developed silicosis.

Key literature references and sources for data

"IDPA Guide for Safe Handling European version - final (low resolution)"

https://www.nepsi.eu/sites/nepsi.eu/files/content/document/file/idpa_guide_for_safe_handling_european_version_-final_low_resolution.pdf

Revision comments

Most of the 16 SECTIONS have been updated and formatted according to the revised ECHA Guidance on the compilation of safety data sheets (version 3.0 of August 2015). Therefore, this SDS has been completely redrafted and replaces the former SDS supplied.

Revision date

07/02/2023

Revision

2

SDS number

24454

ABSODAN Plus

This safety data sheet (SDS) is based on the legal provisions of the REACH Regulation (EC 1907/2006; article 31 and Annex II), as amended. Its contents are intended as a guide to the appropriate precautionary handling of the material. It is the responsibility of recipients of this SDS to ensure that the information contained therein is properly read and understood by all people who may use, handle, dispose or in any way come in contact with the product. Information and instructions provided in this SDS are based on the current state of scientific and technical knowledge at the date of issue indicated. It should not be construed as any guarantee of technical performance, suitability for particular applications, and does not establish a legally valid contractual relationship. This version of the SDS supersedes all previous versions.