Valvoline_{TM}

SAFETY DATA SHEET

Tectyl™ MULTIPURPOSE AMBER RUST PREVENTATIVE

Version: 5.0 Revision Date: 14.04.2020 Print Date: 27/04/2022

Conforms to EU Regulation 1907/2006/EC as amended. - SDSGHS GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Tectyl™ MULTIPURPOSE AMBER

RUST PREVENTATIVE

Product code : 887100

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Corrosion inhibitor.

1.3 Details of the supplier of the safety data

Ellis Enterprises B.V., an affiliate of Valvoline

Wieldrechtseweg 39 3316 BG Dordrecht

Netherlands

+31 (0)78 654 3500 (in the Netherlands), or contact your local CSR contact person

SDS@valvoline.com

1.4 Emergency telephone number

00-800-825-8654 / 001-859-202-3865, or contact your local emergency telephone number at 112

Product Information

+31 (0)78 654 3500 (in the Netherlands), or contact your local CSR contact person

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1 H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

Specific target organ toxicity - single exposure, Category 3, Central nervous

system

H336: May cause drowsiness or dizziness.

Valvoline_{TM}

SAFETY DATA SHEET

Tectyl™ MULTIPURPOSE AMBER RUST PREVENTATIVE

Version: 5.0 Revision Date: 14.04.2020 Print Date: 27/04/2022

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms





Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H336 May cause drowsiness or dizziness.

Supplemental Hazard

Statements

EUH066

Repeated exposure may cause skin

dryness or cracking.

Precautionary statements : P101 If medical advice is needed, have product

container or label at hand.

P102 Keep out of reach of children.

Prevention:

P210 Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other

ignition source.

P251 Do not pierce or burn, even after use.
P271 Use only outdoors or in a well-ventilated

area.

Storage:

P405 Store locked up.

P410 + P412 Protect from sunlight. Do not expose to

temperatures exceeding 50 °C/ 122 °F.

Disposal:

P501 Dispose of contents/ container to an

approved waste disposal plant.

Hazardous components which must be listed on the label:

Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Additional advice

No information available.

SECTION 3: Composition/information on ingredients

SAFETY DATA SHEET

Tectyl™ MULTIPURPOSE AMBER RUST PREVENTATIVE

Version: 5.0 Revision Date: 14.04.2020 Print Date: 27/04/2022

3.2 Mixtures

Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration (%)		
Propane	74-98-6 200-827-9 01-2119486944-21-xxxx	Flam. Gas1; H220 Press. GasLiquefied gas; H280	>= 25,00 - < 40,00		
Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics	64742-48-9 919-857-5 01-2119463258-33-xxxx	Flam. Liq.3; H226 STOT SE3; H336 Asp. Tox.1; H304	>= 20,00 - < 25,00		
Sulfonic acids, petroleum, sodium salts	68608-26-4 271-781-5 01-2119527859-22-xxxx	Eye Irrit.2; H319	>= 1,00 - < 2,50		
2-(2-Heptadec-8-enyl- 2-imidazolin-1- yl)ethanol	95-38-5 202-414-9 01-2119777867-13-xxxx	Acute Tox.4; H302 Skin Corr.1C; H314 Eye Dam.1; H318 STOT RE2; H373 Aquatic Acute1; H400 Aquatic Chronic1; H410	>= 0,10 - < 0,25		
(Z)-N-Methyl-N-(1-oxo- 9-octadecenyl)glycine	110-25-8 203-749-3 01-2119488991-20-xxxx	Acute Tox.4; H332 Skin Irrit.2; H315 Eye Dam.1; H318 Aquatic Acute1; H400	>= 0,10 - < 0,25		
Substances with a workplace exposure limit :					
Butane	106-97-8 203-448-7 01-2119474691-32-xxxx	Flam. Gas1; H220 Press. GasLiquefied gas; H280	>= 15,00 - < 25,00		
(2- Methoxymethylethoxy)p ropanol	34590-94-8 252-104-2 01-2119450011-60-xxxx		>= 1,00 - < 2,50		

For explanation of abbreviations see section 16.

SAFETY DATA SHEET

Tectyl™ MULTIPURPOSE AMBER RUST PREVENTATIVE

Version: 5.0 Revision Date: 14.04.2020 Print Date: 27/04/2022

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Call a POISON CENTRE or doctor/physician if exposed or

you feel unwell.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : Move to fresh air.

If unconscious, place in recovery position and seek medical

advice.

Consult a physician after significant exposure.

In case of skin contact : First aid is not normally required. However, it is

recommended that exposed areas be cleaned by washing

with soap and water.

In case of eye contact : Flush eyes with water as a precaution.

Remove contact lenses. Protect unharmed eye.

If eye irritation persists, consult a specialist.

If swallowed : Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : No symptoms known or expected.

Risks : May cause drowsiness or dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No hazards which require special first aid measures.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Water spray

SAFETY DATA SHEET

Tectyl™ MULTIPURPOSE AMBER RUST **PREVENTATIVE**

Revision Date: 14.04.2020 Print Date: 27/04/2022 Version: 5.0

Foam

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

: Never use welding or cutting torch on or near drum (even

empty) because product (even just residue) can ignite

explosively.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

carbon dioxide and carbon monoxide

Hvdrocarbons sulfur compounds

Aldehydes

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Specific extinguishing

methods

: Product is compatible with standard fire-fighting agents.

Further information : Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations. Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.

> Remove all sources of ignition. Ensure adequate ventilation.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Persons not wearing protective equipment should be excluded

from area of spill until clean-up has been completed.

SAFETY DATA SHEET

Tectyl™ MULTIPURPOSE AMBER RUST PREVENTATIVE

Version: 5.0 Revision Date: 14.04.2020 Print Date: 27/04/2022

Comply with all applicable federal, state, and local regulations.

6.2 Environmental precautions

Environmental precautions

: Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

6.4 Reference to other sections

For further information see Section 8 and Section 13 of the safety data sheet.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

: Open drum carefully as content may be under pressure.

Provide sufficient air exchange and/or exhaust in work rooms.

Do not breathe vapours/dust.

Do not smoke.

Container hazardous when empty.

Take precautionary measures against static discharges. Avoid exposure - obtain special instructions before use. Smoking, eating and drinking should be prohibited in the

application area.

For personal protection see section 8.

Dispose of rinse water in accordance with local and national

regulations.

Advice on protection against

fire and explosion

: Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away

from open flames, hot surfaces and sources of ignition. Use

only explosion-proof equipment.

Hygiene measures : Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Observe label precautions. No smoking.

SAFETY DATA SHEET



Tectyl™ MULTIPURPOSE AMBER RUST PREVENTATIVE

Version: 5.0 Revision Date: 14.04.2020 Print Date: 27/04/2022

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Butane	106-97-8	STEL	750 ppm 1.810 mg/m3	GB EH40
		TWA	600 ppm 1.450 mg/m3	GB EH40
(2- Methoxymethylethoxy)p ropanol	34590-94-8	TWA	50 ppm 308 mg/m3	2000/39/EC
		TWA	50 ppm 308 mg/m3	GB EH40

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

2-(2-Heptadec-8-enyl-2- : End Use: Workers

imidazolin-1-yl)ethanol Exposure routes: Inhalation

Potential health effects: Long-term systemic effects Value: 0,46 mg/m3RD TOX - Repeated dose toxicity

End Use: Workers

Exposure routes: Inhalation

Potential health effects: Acute systemic effects
Value: 14 mg/m3RD TOX - Repeated dose toxicity

End Use: Workers
Exposure routes: Dermal

Potential health effects: Long-term systemic effects Value: 0,06 mg/kgRD TOX - Repeated dose toxicity

End Use: Workers
Exposure routes: Dermal

Potential health effects: Acute systemic effects
Value: 2 mg/kgRD TOX - Repeated dose toxicity

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

2-(2-Heptadec-8-enyl-2- : Sewage treatment plant

SAFETY DATA SHEET

Tectyl™ MULTIPURPOSE AMBER RUST PREVENTATIVE

Version: 5.0 Revision Date: 14.04.2020 Print Date: 27/04/2022

imidazolin-1-yl)ethanol Value: 0,27 mg/l

Fresh water sediment Value: 0,376 mg/kg Marine sediment Value: 0,0376 mg/kg

Soil

Value: 0,075 mg/kg : Sewage treatment plant

octadecenyl)glycine Value: 13 mg/l

8.2 Exposure controls

Engineering measures

(Z)-N-Methyl-N-(1-oxo-9-

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Eye protection : Not required under normal conditions of use. Wear splash-

proof safety goggles if material could be misted or splashed

into eyes.

Hand protection

Material : nitrile rubber
Break through time : 480 min
Glove thickness : 0,38 mm

Remarks : The selected protective gloves have to satisfy the

specifications of Regulation (EU) 2016/425 and the standard

EN 374 derived from it.

The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Skin and body protection : Wear as appropriate:

Impervious clothing

Safety shoes

Flame-resistant clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : In the case of vapour formation use a respirator with an

approved filter.

In the case of dust or aerosol formation use respirator with an

approved filter.

Filter type : Combined particulates, organic gas and low boiling vapour

type (AX-P)

SAFETY DATA SHEET

Tectyl™ MULTIPURPOSE AMBER RUST PREVENTATIVE

Version: 5.0 Revision Date: 14.04.2020 Print Date: 27/04/2022

In the case of vapour formation use a respirator with an approved filter.

In the case of dust or aerosol formation use respirator with an

approved filter.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : aerosol

Colour : amber

Odour : solvent-like

Odour Threshold : No data available

pH : Not applicable

Melting point/freezing point : No data available

Boiling point/boiling range : No data available

Flash point : < 0 °C

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper :

flammability limit

No data available

Lower explosion limit / Lower :

flammability limit

No data available

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : No data available

Density : ca. 0,70 g/cm3 (20 °C)

Solubility(ies)

Water solubility : insoluble

Valvoline_N

SAFETY DATA SHEET

Tectyl™ MULTIPURPOSE AMBER RUST PREVENTATIVE

Version: 5.0 Revision Date: 14.04.2020 Print Date: 27/04/2022

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Oxidizing properties : No data available

9.2 Other information

Self-ignition : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

excessive heat

Do not allow evaporation to dryness.

Exposure to air.

10.5 Incompatible materials

Materials to avoid : Acids

Oxidizing agents salts of strong bases

strong bases

10.6 Hazardous decomposition products

SAFETY DATA SHEET

Tectyl™ MULTIPURPOSE AMBER RUST PREVENTATIVE

Version: 5.0 Revision Date: 14.04.2020 Print Date: 27/04/2022

Hazardous decomposition

products

: No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of : Inhalation

exposure

Skin contact Eye Contact Ingestion

Acute toxicity

Not classified based on available information.

Components:

PROPANE:

Acute inhalation toxicity : LC50 (Rat): 1.237 mg/l

Exposure time: 2 h
Test atmosphere: gas

Assessment: Not classified as acutely toxic by inhalation

under GHS.

Remarks: Information given is based on data obtained from

similar substances.

Components:

Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics:

Acute oral toxicity : LD50 (Rat, male and female): > 15.000 mg/kg

Method: OECD Test Guideline 423

Remarks: Information given is based on data obtained from

similar substances.

Acute inhalation toxicity : LC50 (Rat): > 4,95 mg/l

Exposure time: 4 h

Test atmosphere: vapour

Method: OECD Test Guideline 403

Assessment: No adverse effect has been observed in acute

inhalation toxicity tests.

Remarks: Information given is based on data obtained from

similar substances.

Acute dermal toxicity : LD50 (Rabbit, male and female): >= 3.160 mg/kg

Method: OECD Test Guideline 402

Assessment: No adverse effect has been observed in acute

dermal toxicity tests.

SAFETY DATA SHEET

Tectyl™ MULTIPURPOSE AMBER RUST PREVENTATIVE

Version: 5.0 Revision Date: 14.04.2020 Print Date: 27/04/2022

Remarks: Information given is based on data obtained from

similar substances.

Components:

SODIUM PETROLEUM SULFONATE:

Acute oral toxicity : LD50 (Rat): > 5 g/kg

LD50 (Rat): > 5.000 mg/kg

Method: OECD Test Guideline 401

GLP: yes

Remarks: Information given is based on data obtained from

similar substances.

Acute inhalation toxicity : LC50 (Rat): > 1,9 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

GLP: yes

Assessment: The component/mixture is classified as acute

inhalation toxicity, category 5.

Remarks: No mortality observed at this dose.

Information given is based on data obtained from similar

substances.

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

Method: OECD Test Guideline 402

GLP: yes

Remarks: No mortality observed at this dose.

Information given is based on data obtained from similar

substances.

Components:

OLEYL HYDROXYETHYL IMIDAZOLINE:

Acute oral toxicity : LD50 (Rat): ca. 1.265 mg/kg

Components:

OLEYL N-METHYLGLYCINE:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 1,01 - 1,85 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Components:

BUTANE NORMAL:

SAFETY DATA SHEET

Tectyl™ MULTIPURPOSE AMBER RUST PREVENTATIVE

Version: 5.0 Revision Date: 14.04.2020 Print Date: 27/04/2022

Acute inhalation toxicity : LC50 (Mouse): 680 mg/l

Exposure time: 2 h

LC50 (Rat): > 50000 ppm Exposure time: 2 h Test atmosphere: gas

Components:

DIPROPYLENE GLYCOL MONOMETHYL ETHER:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC0 (Rat, female): > 553 ppm

Exposure time: 8 h
Test atmosphere: vapour

Method: OECD Test Guideline 403

Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rat): > 5.000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Components:

Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics:

Result: Slight, transient irritation

SODIUM PETROLEUM SULFONATE:

Species: Rabbit

Result: Slight, transient irritation

Remarks: Information given is based on data obtained from similar substances.

OLEYL HYDROXYETHYL IMIDAZOLINE:

Species: Rabbit

Method: OECD Test Guideline 404

Result: Corrosive after 1 to 4 hours of exposure

OLEYL N-METHYLGLYCINE:

Species: Rabbit

Result: Irritating to skin.

DIPROPYLENE GLYCOL MONOMETHYL ETHER:

Species: Rabbit

Result: No skin irritation

SAFETY DATA SHEET

Tectyl™ MULTIPURPOSE AMBER RUST PREVENTATIVE

Version: 5.0 Revision Date: 14.04.2020 Print Date: 27/04/2022

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Unlikely to cause eye irritation or injury.

Components:

Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics:

Result: No eye irritation

SODIUM PETROLEUM SULFONATE:

Species: Rabbit

Result: Irritating to eyes.

Remarks: Information given is based on data obtained from similar substances.

OLEYL HYDROXYETHYL IMIDAZOLINE:

Result: Corrosive

OLEYL N-METHYLGLYCINE:

Species: Rabbit Result: Corrosive

DIPROPYLENE GLYCOL MONOMETHYL ETHER:

Species: Rabbit

Result: Slight, transient irritation

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information. Respiratory sensitisation: Not classified based on available information.

Components:

SODIUM PETROLEUM SULFONATE:

Assessment: Does not cause skin sensitisation.

Remarks: Information given is based on data obtained from similar substances.

OLEYL HYDROXYETHYL IMIDAZOLINE:

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

Method: OECD Test Guideline 406

OLEYL N-METHYLGLYCINE:

Test Type: Maximisation Test

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

DIPROPYLENE GLYCOL MONOMETHYL ETHER:

SAFETY DATA SHEET



Tectyl™ MULTIPURPOSE AMBER RUST PREVENTATIVE

Version: 5.0 Revision Date: 14.04.2020 Print Date: 27/04/2022

Species: Humans

Assessment: Does not cause skin sensitisation.

Germ cell mutagenicity

Not classified based on available information.

Components:

PROPANE:

Genotoxicity in vitro : Test Type: Ames test

Test species: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative

Remarks: Information given is based on data obtained from

similar substances.

SODIUM PETROLEUM SULFONATE:

Genotoxicity in vitro : Test Type: Ames test

Test species: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative

Remarks: Information given is based on data obtained from

similar substances.

OLEYL N-METHYLGLYCINE:

Genotoxicity in vitro : Test Type: Ames test

Test species: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative

BUTANE NORMAL:

Genotoxicity in vitro : Test Type: Ames test

Test species: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative

DIPROPYLENE GLYCOL MONOMETHYL ETHER:

Genotoxicity in vitro : Test Type: Ames test

Test species: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative

Carcinogenicity

Not classified based on available information.

Components:

Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation

SAFETY DATA SHEET

Tectyl™ MULTIPURPOSE AMBER RUST PREVENTATIVE

Version: 5.0 Revision Date: 14.04.2020 Print Date: 27/04/2022

Assessment

(EC) 1272/2008, Annex VI, Part 3, Note L)

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause drowsiness or dizziness.

Components:

Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics:

Assessment: May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Components:

OLEYL HYDROXYETHYL IMIDAZOLINE:

Exposure routes: Ingestion

Target Organs: Gastrointestinal tract, thymus gland

Assessment: May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

Components:

Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

Components:

DIPROPYLENE GLYCOL MONOMETHYL ETHER:

Remarks: Central nervous system

SECTION 12: Ecological information

SAFETY DATA SHEET

Tectyl™ MULTIPURPOSE AMBER RUST **PREVENTATIVE**

Version: 5.0 Revision Date: 14.04.2020 Print Date: 27/04/2022

12.1 Toxicity

Components:

Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 1.000 mg/l

> Exposure time: 96 h Test Type: semi-static test Test substance: WAF

Method: OECD Test Guideline 203

aquatic invertebrates

Toxicity to daphnia and other : EL50 (Daphnia magna (Water flea)): 1.000 mg/l

Exposure time: 48 h Test Type: static test Test substance: WAF

Method: OECD Test Guideline 202

Toxicity to algae : EL50 (Pseudokirchneriella subcapitata (green algae)): > 1.000

mg/l

End point: Growth inhibition Exposure time: 72 h Test Type: static test

Method: OECD Test Guideline 201

Sulfonic acids, petroleum, sodium salts

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 1.000 mg/l

> Exposure time: 96 h Test Type: Renewal Test substance: WAF

Method: OECD Test Guideline 203

GLP: yes

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): > 1.000 mg/l

Exposure time: 48 h Test Type: static test Test substance: WAF

Remarks: Information given is based on data obtained from

similar substances.

Toxicity to algae : NOEC (Pseudokirchneriella subcapitata (green algae)): >

1.000 mg/l

End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF

Remarks: Information given is based on data obtained from

similar substances.

2-(2-Heptadec-8-enyl-2-imidazolin-1-yl)ethanol

SAFETY DATA SHEET

Tectyl™ MULTIPURPOSE AMBER RUST **PREVENTATIVE**

Revision Date: 14.04.2020 Print Date: 27/04/2022 Version: 5.0

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 0.3 mg/l

> Exposure time: 96 h Test Type: static test

Method: OECD Test Guideline 203

Toxicity to daphnia and other EC50 (Daphnia magna (Water flea)): 0,163 mg/l

aquatic invertebrates Exposure time: 48 h Test Type: semi-static test

Method: OECD Test Guideline 202

: EC50 (Desmodesmus subspicatus (green algae)): 0.03 mg/l Toxicity to algae

End point: Growth inhibition

Exposure time: 72 h Test Type: static test

Method: OECD Test Guideline 201

M-Factor (Short-term (acute) 10

aquatic hazard)

M-Factor (Long-term : 1

(chronic) aquatic hazard)

(Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): 9,3 mg/l

> Exposure time: 96 h Test Type: static test

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 0,43 mg/l

Exposure time: 48 h Test Type: static test

Toxicity to algae : EC50 (Desmodesmus subspicatus (green algae)): 6,3 mg/l

End point: Growth inhibition

Exposure time: 72 h Test Type: static test

Butane

: Remarks: No toxicity at the limit of solubility Toxicity to fish

QSAR

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): Expected > 10 - < 100

Exposure time: 48 h Remarks: **QSAR**

Toxicity to algae : EC50 (green algae): Expected 7,7 mg/l

Exposure time: 96 h Remarks: QSAR

SAFETY DATA SHEET

Tectyl™ MULTIPURPOSE AMBER RUST **PREVENTATIVE**

Version: 5.0 Revision Date: 14.04.2020 Print Date: 27/04/2022

(2-Methoxymethylethoxy)propanol

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 10.000 mg/l

> Exposure time: 96 h Test Type: static test

aquatic invertebrates

Toxicity to daphnia and other : LC50 (Daphnia magna (Water flea)): 1.919 mg/l

Exposure time: 48 h

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): > 969

End point: Growth inhibition

Exposure time: 72 h

12.2 Persistence and degradability

Components:

Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics

Biodegradability : Result: Readily biodegradable.

Biodegradation: 80 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Sulfonic acids, petroleum, sodium salts

Biodegradability : Result: Not readily biodegradable.

> Biodegradation: 8 % Exposure time: 28 d

Method: OECD Test Guideline 301D

Remarks: Information given is based on data obtained from

similar substances.

2-(2-Heptadec-8-enyl-2-imidazolin-1-yl)ethanol

: Result: Not readily biodegradable. Biodegradability

Biodegradation: 1 % Exposure time: 28 d

Method: OECD Test Guideline 301B

(Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine

: Result: Readily biodegradable. Biodegradability

> Biodegradation: 85 % Exposure time: 28 d

Method: OECD Test Guideline 301B

Butane

Biodegradability : Result: Readily biodegradable.

Remarks: Information given is based on data obtained from

similar substances.

SAFETY DATA SHEET

Tectyl™ MULTIPURPOSE AMBER RUST PREVENTATIVE

Version: 5.0 Revision Date: 14.04.2020 Print Date: 27/04/2022

(2-Methoxymethylethoxy)propanol

Biodegradability : Result: Readily biodegradable.

Biodegradation: 75 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Chemical Oxygen Demand : 2,02 mg/g

(COD)

ThOD : 2,06 mg/g

12.3 Bioaccumulative potential

Components:

Propane

Partition coefficient: n- : log Pow: 2,36

octanol/water

Sulfonic acids, petroleum, sodium salts

Partition coefficient: n- : log Pow: Calculated > 10

octanol/water

2-(2-Heptadec-8-enyl-2-imidazolin-1-yl)ethanol

Partition coefficient: n- : log Pow: 8

octanol/water

(Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine

Partition coefficient: n- : log Pow: 3,5 - 4,2

octanol/water

Butane

Partition coefficient: n- : log Pow: 2,89

octanol/water

(2-Methoxymethylethoxy)propanol

Partition coefficient: n- : log Pow: 0,004

octanol/water

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or

Valvoline_{TM}

SAFETY DATA SHEET

Tectyl™ MULTIPURPOSE AMBER RUST PREVENTATIVE

Version: 5.0 Revision Date: 14.04.2020 Print Date: 27/04/2022

very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher..

12.6 Other adverse effects

Product:

Additional ecological

information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to aquatic life.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Empty containers should be taken to an approved waste

handling site for recycling or disposal.

Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

14.1 UN number

ADN : UN 1950
ADR : UN 1950
RID : UN 1950
IMDG : UN 1950
IATA : UN 1950

14.2 UN proper shipping name

ADN : AEROSOLS
ADR : AEROSOLS
RID : AEROSOLS
IMDG : AEROSOLS

SAFETY DATA SHEET

Tectyl™ MULTIPURPOSE AMBER RUST PREVENTATIVE

Version: 5.0 Revision Date: 14.04.2020 Print Date: 27/04/2022

IATA : AEROSOLS

14.3 Transport hazard class(es)

ADN : 2
ADR : 2
RID : 2
IMDG : 2.1
IATA : 2.1

14.4 Packing group

ADN

Packing group : Not assigned by regulation

Classification Code : 5F Labels : 2.1

ADR

Packing group : Not assigned by regulation

Classification Code : 5F Labels : 2.1 Tunnel restriction code : (D)

RID

Packing group : Not assigned by regulation

Classification Code : 5F Hazard Identification Number : 23 Labels : 2.1

IMDG

Packing group : Not assigned by regulation

Labels : 2.1 EmS Code : F-D, S-U

IATA (Cargo)

Packing instruction (cargo : 203

aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

Labels : Flammable Gas

IATA (Passenger)

Packing instruction : 203

(passenger aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

Labels : Flammable Gas

14.5 Environmental hazards

Valvoline_{TM}

SAFETY DATA SHEET

Tectyl™ MULTIPURPOSE AMBER RUST PREVENTATIVE

Version: 5.0 Revision Date: 14.04.2020 Print Date: 27/04/2022

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1005/2009 on substances that

deplete the ozone layer

: Not applicable

Regulation (EC) No 850/2004 on persistent organic

pollutants

Not applicable

REACH - List of substances subject to authorisation

(Annex XIV)

Not applicable

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

: Not applicable

Regulation (EC) No 649/2012 of the European

Parliament and the Council concerning the export and

import of dangerous chemicals

Not applicable

Valvoline_{TM}

SAFETY DATA SHEET

Tectyl™ MULTIPURPOSE AMBER RUST PREVENTATIVE

Version: 5.0 Revision Date: 14.04.2020 Print Date: 27/04/2022

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

preparations and articles (Annex XVII)

: Not applicable

Quantity 1 Quantity 2

8 Extremely flammable 10 t 50 t

9b Dangerous for the 200 t 500 t

environment

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of

major-accident hazards involving dangerous substances.

P3a FLAMMABLE AEROSOLS 150 t 500 t

18 Liquefied extremely 50 t 200 t

flammable gases (including LPG) and natural gas

Other regulations:

Young people under 18 years old are not allowed to work with this product according to the EU Directive 94/33/EC on the protection of young people at work.

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI: On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

TCSI : Not in compliance with the inventory

Valvoline_m

SAFETY DATA SHEET

Tectyl™ MULTIPURPOSE AMBER RUST PREVENTATIVE

Version: 5.0 Revision Date: 14.04.2020 Print Date: 27/04/2022

TSCA : On TSCA Inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

15.2 Chemical safety assessment

No data available

SECTION 16: Other information

Further information

Internal information: R0524073

Full text of H-Statements

H220	Extremely flammable gas.
H226	Flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure
	if swallowed.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Other information

: The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department ('+31 (0)78 654 3500).

SAFETY DATA SHEET

Tectyl™ MULTIPURPOSE AMBER RUST PREVENTATIVE

Version: 5.0 Revision Date: 14.04.2020 Print Date: 27/04/2022

Sources of key data used to compile the Safety Data Sheet

Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet:

ACGIH: American Conference of Industrial Hygienists

BEI: Biological Exposure Index

CAS: Chemical Abstracts Service (Division of the American Chemical Society).

CMR: Carcinogenic, Mutagenic or Toxic for Reproduction

FG: Food grade

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization

ICAO-TI (ICAO): Technical Instructions by the "International Civil Aviation Organization"

IMDG: International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

logPow: octanol-water partition coefficient

LCxx: Lethal Concentration, for xx percent of test population

LDxx: Lethal Dose, for xx percent of test population. ICxx: Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx N.O.S.: Not Otherwise Specified

OECD: Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic

PPE: Personal Protective Equipment STEL: Short-term exposure limit STOT: Specific Target Organ Toxicity

TLV : Threshold Limit Value TWA : Time-weighted average

vPvB: Very Persistent and Very Bioaccumulative

WEL: Workplace Exposure Level

ABM: Water Hazard Class for the Netherlands

ADR: Agreement concerning the International Carriage of Dangerous Goods by Road.

ADNR: Regulation for the Carriage of Dangerous Substances on the Rhine

CLP: Classification, Labelling and Packaging

CSA: Chemical Safety Assessment CSR: Chemical Safety Report



SAFETY DATA SHEET

Tectyl™ MULTIPURPOSE AMBER RUST PREVENTATIVE

Version: 5.0 Revision Date: 14.04.2020 Print Date: 27/04/2022

DNEL: Derived No Effect Level.

EINECS: European Inventory of Existing Commercial Chemical Substances.

ELINCS: European List of Notified Chemical Substances

PEC : Predicted Effect Concentration PEL : Permissible Exposure Limits

PNEC: Predicted No Effect Concentration

R-phrase: Risk phrase

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail

S-phrase: Safety phrase

WGK: German Water Hazard Class