



## INDUSTRIAL DEGREASER FG

### HEAVY DUTY NON-CHLORINATED CLEANER

Industrial Degreaser FG is an excellent general purpose solvent degreaser, formulated for use in the food/ beverage industry to tackle “difficult” degreasing applications.

Industrial Degreaser FG is an innovative solvent blend that is excellent for use where rapid turnaround is necessary and low flash point solvents can be used. Dissolves and removes greases, oils, lubricants, adhesives and contaminants from equipment, machinery, motors and metal parts.

Industrial Degreaser FG cuts through dirt and grease and has a fast evaporation rate to minimise downtime, leaving no residues. Easy “in place” cleaning with minimal odour. Non-corrosive and non-staining.



Cleaners



360° Spray System for all angle use



NSF Registered:  
Aerosol A8 + K1 (N° 140255)  
Bulk A8 + K1 (N° 140250)



Just one of over 25 FG products

### PRODUCT CODES / FILL SIZES



30251 / 500ml



30252 / 5Ltr

### APPLICATIONS

- Bearings
- General degreasing and oil removal
- Electric motors
- Mechanical brakes and clutches
- Air tools
- Pumps
- Material handling equipment
- Dies
- Generators
- Wire ropes
- Moulds
- Chains

### DIRECTIONS

- Can be used by spraying, immersion, dipping or wiping
- For tough soiling, apply product and agitate to loosen contaminants
- Apply liberally and allow excess to run off
- Air dry or dry with absorbent cloth. Repeat if necessary
- Test a small area prior to use to check materials compatibility.
- Do not use on sensitive electronic equipment
- Ensure adequate ventilation.
- Do not use on energised equipment
- Allow to dry thoroughly and vapours disperse before reactivating system.

## TECHNICAL DATA (WITHOUT PROPELLANT)

Appearance	Colourless liquid
Odour	Sweet Odour
Specific Gravity (@ 20°C)	0.808
Flash Point (closed cup)	25°C
Boiling Range	100-170 °C
Freezing Point	< -30 °C
Evaporation Rate (ether = 1)	19
Vapour Density (vs air = 1)	4
Kauri-Butanol Value	> 150
Hildebrand Solubility Parameter (calc.)	8.206
Hydrogen Bonding Index (calc.)	0.384
Fractional Polarity (calc.)	0.037
Viscosity (@ 20°C, calc.)	0.76 mPa.s
Surface Tension (@ 25°C est.)	23 mN/m

## MATERIALS COMPATIBILITY

OK	Safe On Most Plastics (Test Prior To Use)
CAUTION	-
NOT OK	-

## STORAGE & SHELF LIFE

The product may be stored at normal ambient temperatures and has a shelf life of not less than 6 years with correct storage. Aerosols should always be stored below 50°C, away from direct heat and naked flame.

## HEALTH AND SAFETY

A separate Safety Data Sheet (SDS) according to EC Regulation 73/404/EEC and 648/2004/EC is available from Ambersil.com or via [info.uk@crcind.com](mailto:info.uk@crcind.com)

## MISREPRESENTATION ACT 1967

## TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

Version 3.0  
Created: July 2019  
Updated: August 2020

CRC Industries UK Ltd.  
Wylde Road, Bridgwater  
Somerset, TA6 4DD  
United Kingdom

t +44 (0)1278 727200  
f +44 (0)1278 425644  
e [sales.uk@crcind.com](mailto:sales.uk@crcind.com)  
w [www.ambersil.com](http://www.ambersil.com)

Company Registered No. 04910479

VAT No. GB 821 5195 42

