

**Specialty
Lubricants**

**MOLYKOTE® PG 75
High Performance Grease**

FEATURES

- Suitable for long-term lubrication
- Good low temperature characteristics (usable down to -40°C)
- Very low coefficient of friction
- Compatible with many plastics and elastomers

COMPOSITION

- Mineral oil
- Polyalphaolefine
- Lithium soap
- Solid lubricants

Lubricating grease for plastic/plastic and plastic/metal combinations with slow to medium-fast movements and light loads

APPLICATION

- Used on vehicle track-rod joints.

TYPICAL PROPERTIES

Specifications writers: These values are not intended for use in preparing specifications. Please contact your local Dow Corning sales representative prior to writing specifications on this product.

Standard	Test	Unit	Result
	Color		Beige
	Consistency, density, viscosity		
DIN 51 818	NLGI consistency class		Approx. 2
ISO 2137	Worked penetration	mm/10	270-300
ISO 2811	Density at 20°C	g/ml	0.86
DIN 51 562	Base oil viscosity at 40°C	mm ² /s	32
	Temperature		
	Service temperature	°C	-40 to +130
ISO 2176	Drop point	°C	>190
ASTM-D147880	Low temperature torque test at -30°C		
	Initial break-away torque	Nm	222x10 ⁻³
	Torque after 20 minutes running time	Nm	36x10 ⁻³
DIN 51 805	Kesternich method - flow pressure at -20°C	mbar	280
	Load-carrying capacity, wear protection, service life		
	Four-ball tester (VKA)		
DIN 51 350 pt.4	Weld load	N	1300
DIN 51 350 pt.5	Wear scar under 400N load	mm	0.8
	Coefficient of friction		
	Steel ball against plastic surface (POM) dia (ball) = 12.7mm; load = 5N; v = 10cm/s, 24h, μ=		0.02
	Corrosion protection		
DIN 51 802	SKF-Emcor method Degree of corrosion		1-2
	Oil separation - evaporation		
DIN 51 817	Standard test	%	4.8
FD 791-32/2	Oil bleeding, 24h, 100°C	%	2.4
FD 791-32/2	Oil evaporation, 24h, 100°C	%	0.2

HOW TO USE

How to apply

Clean points of contact. Apply in same way as lubricating greases, using brush, spatula, grease-gun or automatic lubricating device. Suitable for delivery by central lubricating system. In the event of long breaks in service e.g. overnight, the pressure in the delivery equipment should be relieved. Not to be mixed with other greases.

Because of variation in quality of plastics and elastomers, compatibility tests should be carried out for swelling and shrinkage, stress-crack formation, and changes in strength and hardness.

HANDLING PRECAUTIONS

PRODUCT SAFETY INFORMATION REQUIRED FOR SAFE USE IS NOT INCLUDED. BEFORE HANDLING, READ PRODUCT AND SAFETY DATA SHEETS AND CONTAINER LABELS FOR SAFE USE, PHYSICAL AND HEALTH HAZARD INFORMATION. THE SAFETY DATA SHEET IS AVAILABLE FROM YOUR LOCAL DOW CORNING SALES REPRESENTATIVE.

USABLE LIFE AND STORAGE

When stored at or below 20°C in the original unopened containers, this product has a usable life of 60 months from the date of production.

PACKAGING

This product is available in different standard container sizes. Detailed container size information should be obtained from your nearest Dow Corning sales office or Dow Corning distributor.

LIMITATIONS

This product is neither tested nor represented as suitable for medical or pharmaceutical uses.

HEALTH AND ENVIRONMENTAL INFORMATION

To support customers in their product safety needs, Dow Corning has an extensive Product Stewardship organization and a team of Health, Environment and Regulatory Affairs specialists available in each area.

For further information, please consult your local Dow Corning representative.

LIMITED WARRANTY - PLEASE READ CAREFULLY

The information contained herein is offered in good faith based on Dow Corning's research and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information shall not be used in substitution for customers' tests to ensure that Dow Corning's products are fully satisfactory for your specific applications. Dow Corning's sole warranty is that the product will meet its current sales specifications. Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted. DOW CORNING SPECIFICALLY DISCLAIMS ANY OTHER EXPRESS OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY. UNLESS DOW CORNING PROVIDES YOU WITH A SPECIFIC, DULY SIGNED ENDORSEMENT OF FITNESS FOR USE, DOW CORNING DISCLAIMS LIABILITY FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. SUGGESTIONS OF USE SHALL NOT BE TAKEN AS INDUCEMENTS TO INFRINGE ANY PATENT.

Your Global Connection

At home or abroad - wherever your business takes you - you'll find the product supply, customer service and technical support you need to succeed available locally from Dow Corning. Whether you face a challenge that could benefit from Dow Corning's international experience, or you need a reliable, local source of supply for innovative solutions, just pick up the phone and call us.

To consult Dow Corning web site, type: www.dowcorning.com

DOW CORNING ASIA

Australia & New Zealand

Dow Corning Australia Pty Ltd.

Tel.: +61 1300 360 732

Fax: +61 2984 741 00

China

Dow Corning China Ltd.

Tel.: +86 21 6249 2316

Fax: +86 21 6249 2317

China

Dow Corning Asia (H.K.)

Tel.: +852 2835 0350

Fax: +852 2836 6650

India, Indonesia, Singapore, Malaysia & Philippines

Dow Corning Singapore Pte Ltd.

Tel.: +65 253 6611

Fax: +65 253 6070

Japan

Dow Corning Asia Ltd.

Tel.: +81 3 3287 1151

Fax: +81 3 3287 1059 & 1081

Japan

Dow Corning Toray Silicone Co Ltd.

Tel.: +81 3 3287 1010

Fax: +81 3 3287 1201

Korea

Dow Corning Korea Ltd.

Tel.: +82 2 551 7600

Fax: +82 2 551 6800

Taiwan

Dow Corning Taiwan Inc.

Tel.: +886 2 2713 6936

Fax: +886 2 2717 2209

Thailand

Dow Corning Thailand Ltd.

Tel.: +66 2 326 0773

Fax: +66 2 326 0767

DOW CORNING EUROPE

Germany, Austria, Switzerland & Eastern Europe

Dow Corning GmbH

GERMANY

Tel.: +49 (0)611 - 23 71

Fax: +49 (0)611 - 237 610

France & North Africa

Dow Corning France S.A.

Tel.: +33 (0)4 72 84 13 60

Fax: +33 (0)4 72 84 13 79

Italy & Eastern Mediterranean Countries

Dow Corning S.p.A.

ITALY

Tel.: +39 039 - 60 711

Fax: +39 039 - 68 996 60

Poland

Dow Corning Polska Sp. zo.o.

Tel.: +48 (0)22 645 14 46

Fax: +48 (0)22 645 14 40

United Kingdom, Eire, Nordic Countries, Benelux, South Africa & Middle East

Dow Corning

UNITED KINGDOM

Tel.: +44 (0)1 676 52 80 00

Fax: +44 (0)1 676 52 80 01

Spain & Portugal

Dow Corning Ibérica S.A.

SPAIN

Tel.: +34 93 36 36 900

Fax: +34 93 36 36 901

DOW CORNING NORTH AMERICA

Dow Corning Corporation

Tel.: +1 517 496 6000

Fax: +1 517 496 8026

DOW CORNING SOUTH AMERICA

Dow Corning do Brasil Ltda.

Tel.: +55 11 3759 4300

Fax: +55 11 3758 5727