



KP2K-20

GLS 135/N2

Special grease

ELKALUB GLS 135/N2 is a lithium-saponified, water resistant and corrosion inhibiting universal grease. It can be used for roller and slide bearings in the temperature range from -20 °C to +120 °C. The short-fibred and homogeneous grease is excellently suitable for the lubrication of linear guidance systems as well as for ball bearings up to a speed factor ndm of 500.000. ELKALUB GLS 135/N2 has a very low oil bleeding and separation tendency. Therefore it is well conveyable in central lubricating systems (conveying test at bielomatik and Lincoln).

BASE OIL ester mineral oil

THICKENER Lithium special

VISCOSITY 100 mm²/s

OPERATING TEMPERATURE -20 °C bis 120 °C

NLGI CLASS 2

FIELD OF USE

- roller bearing
- bearings
- Linear guides & ball screws
- Guides & Curves

BUSINESS

- print

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo–Fr 09–16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- drive technology
- Wood
- bearing manufacturer
- plant construction

FUNCTIONALITY

- noise

PACKING

- 250 g tube
 - 100 g cartridge
 - 380 g LubeShuttle
 - 400 g cartridge
 - 1 kg can
 - 5 kg bucket
 - 18 kg hobbock
 - 50 kg hobbock
 - 150 kg barrel
-

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com